SSL Conversions – The original Scandinavian style camper converters

Bespoke timber clad van-to-camper conversions, hand crafted with great attention to detail by qualified motorhome technicians with over 20 years' experience.

MAINTENANCE OF TIMBER WORKTOPS & CLADDING

Instructions on how to care for your solid wood worktop

Please pay particular attention to the 'oiling' and 'temperature' sections

AFTERCARE INSTRUCTIONS - WORKTOPS

a) **Spillages:** Spillages must be immediately wiped away with a clean dry cloth and not allowed to stand on the worktop for any length of time.

b) **Direct cutting/chopping:** Cutting or chopping food (or anything else) directly on the worktop will damage it; please use a chopping board or butchers block.

c) **Direct contact:** Do not place hot, wet or dirty pots and pans directly on to the worktop. Stainless steel hot-rods or trivets can be purchased to protect your worktops from these items. Tin/aluminium cans, iron, copper or steel containers could stain the timber and should be kept away from the wood worktop.

d) **Cleaning:** Wipe worktops down with a damp lint-free cloth using warm water and a small amount of soap. Do not use any multi-purpose cleaning products which contain chemicals as they may damage the worktop. Avoid using scouring pads. Wipe excess liquids off the worktop.

e) **Oiling:** Wooden worktops need to be regularly oiled to keep their fine quality finish and long, trouble-free life. We use Liberon Tung Oil. There is no set-in-stone routine for oiling, it all depends on the environment and usage of the kitchen. We recommend worktops are oiled once a month for the first 6 months and then once every 3 months after that if required. In general, when a worktop becomes dull or patchy, and when water stops forming into droplets or water beads on the surface, that's a good indication that a coat of oil needs to be applied.

AFTERCARE INSTRUCTIONS - WORKTOPS

f) **Temperature:** Wood is, of course, a natural product and will react to its environment. If your leisure vehicle is going to be laid up for any length of time, especially during a period of damp and cold weather conditions, we highly recommend leaving an oil filled radiator on inside the vehicle so as to prevent bowing of wooden worktops.

Instructions on how to care for your timber cladding

Please pay particular attention to the 'oiling' and 'temperature' sections

AFTERCARE INSTRUCTIONS - CLADDING

a) **Spillages:** Spillages must be immediately wiped away with a clean dry cloth and not allowed to settle on the cladding for any length of time.

b) **Cleaning:** Wipe cladding down with a damp lint-free cloth using warm water and a small amount of soap. Do not use any multi-purpose cleaning products which contain chemicals as they may damage the timber. Avoid using scouring pads. Wipe excess liquids off the cladding.

c) **Oiling:** Timber cladding needs to be regularly oiled to keep its quality finish and long, trouble-free life. We use Colron Danish Oil Natural. There is no set-in-stone routine for oiling; it all depends on the environment and usage of the kitchen. If new worktops are treated frequently a protective layer builds up and over time will require less oiling. We recommend cladding is oiled once a month for the first 6 months following installation, and then once every 3 months after that if required.

d) **Temperature:** Wood is, of course, a natural product and will react to its environment. If your leisure vehicle is going to be laid up for any length of time, especially during a period of damp and cold weather conditions, we highly recommend leaving an oil filled radiator on inside the vehicle so as to prevent bowing of wooden worktops.